



General dimensions	
ØA:	36.5mm
K:	24mm
P:	31mm
R:	25.3mm
ØY:	3.2mm
J:	2.8mm

### Specifications:

Series: 92  
 Gender: Plug/Female  
 Format: Receptacle with Coupling Nut  
 Connector size: T20  
 Number of contacts: 6  
 Shell: Aluminium alloy  
 Connector plating: Black (2)  
 Coupling: Screwlock  
 Insulator: Thermo-hard  
 Mating cycles: 500+  
 Adjustable cable gland: n/a  
 Ingress protection: IP67 when mated  
 Resistant to saline atmosphere 600h ASTM B-117

Contacts: Copper alloy  
 Contact plating: Gold over nickel  
 Termination method: Solder  
 Max wire section: 3 x 1.75 mm<sup>2</sup> & 3 x 5.1mm<sup>2</sup>  
 Max contact resistance: 0.005Ω  
 Working voltage: 300V ac  
 Test voltage: 1.400V ac  
 Working current: 3 x 10A & 3 x 25A

### Part Number: 92 09 26R00 0 S 0 2 0

Series: 92  
 Type: Receptacle with C/N  
 Insulator planform: 26R  
 Polarisation: Standard  
 Gender: Plug/Female  
 Cable clamp: n/a  
 Finish: Black (non-conductive)  
 Seal protection: Standard

