



| General dimensions | |
|--------------------|-------|
| ØA: | 52mm |
| K: | 34mm |
| P: | 46mm |
| T: | 4mm |
| ØV: | 35mm |
| ØY: | 3.5mm |
| J: | 2.8mm |
| N: | 26.5 |

Specifications:

| | |
|--------------------------------|------------------------------|
| Series: | 92 |
| Gender: | Plug/Male |
| Format: | Receptacle with Coupling Nut |
| Connector size: | T30 |
| Number of contacts: | 7 |
| Shell: | Aluminium alloy |
| Connector plating: | Black (2) |
| Coupling | Screwlock |
| Insulator: | Thermo-hard |
| Mating cycles: | 500+ |
| Adjustable cable gland: | n/a |
| Ingress protection: | IP67 when mated |
| Resistant to saline atmosphere | 600h ASTM B-117 |

| | |
|-------------------------|--|
| Contacts: | Copper alloy |
| Contact plating: | Gold over nickel |
| Termination method: | Solder |
| Max wire section: | 6 x 5.1mm ² & 1 x 13mm ² |
| Max contact resistance: | 0.005Ω |
| Working voltage: | 470V ac |
| Test voltage: | 1.750V ac |
| Working current: | 6 x 25A & 1 x 50A |

Part Number: 92 09 37Y00 0 P 0 2 0

| |
|--------------------------------|
| Series: 92 |
| Type: Receptacle with C/N |
| Insulator planform: 37Y |
| Polarisation: Standard |
| Gender: Plug/Male |
| Cable clamp: n/a |
| Finish: Black (non-conductive) |
| Seal protection: Standard |

