



| General dimensions | |
|--------------------|---------|
| E: | 81mm |
| ØQ: | 46mm |
| ØC: | 11-21mm |

Specifications:

| | |
|--------------------------------|-----------------|
| Series: | 92 |
| Gender: | Socket/Male |
| Format: | Extender |
| Connector size: | T30 |
| Number of contacts: | 15 |
| Shell: | Aluminium alloy |
| Connector plating: | Black (2) |
| Coupling | Screwlock |
| Insulator: | Thermo-hard |
| Mating cycles: | 500+ |
| Adjustable cable gland: | G (11-21mm) |
| Ingress protection: | IP67 when mated |
| Resistant to saline atmosphere | 600h ASTM B-117 |

| | |
|-------------------------|--|
| Contacts: | Copper alloy |
| Contact plating: | Gold over nickel |
| Termination method: | Solder |
| Max wire section: | 11 x 1.75mm ² & 4 x 5.1mm ² |
| Max contact resistance: | 0.005Ω |
| Working voltage: | 355V ac |
| Test voltage: | 1.750V ac |
| Working current: | 11 x 10A & 4 x 25A |

Part Number: 92 01 315K0 0 P G 2 0

Series: 92

Type: Extender

Insulator planform: 315K

Polarisation: Standard

Gender: Socket/Male

Cable clamp: G (11-21mm)

Finish: Black (non-conductive)

Seal protection: Standard

