



General dimensions	
F:	90mm
ØX:	44.5mm
ØC:	18-25mm

### Specifications:

Series: 92  
 Gender: Socket/Female  
 Format: Extender  
 Connector size: T30  
 Number of contacts: 7  
 Shell: Aluminium alloy  
 Connector plating: Black (2)  
 Coupling: Screwlock  
 Insulator: Thermo-hard  
 Mating cycles: 500+  
 Adjustable cable gland: G (18-25mm)  
 Ingress protection: IP67 when mated  
 Resistant to saline atmosphere 600h ASTM B-117

Contacts: Copper alloy  
 Contact plating: Gold over nickel  
 Termination method: Solder  
 Max wire section: 6 x 5.1mm<sup>2</sup> & 1 x 13mm<sup>2</sup>  
 Max contact resistance: 0.005Ω  
 Working voltage: 470V ac  
 Test voltage: 1.750V ac  
 Working current: 6 x 25A & 1 x 50A

### Part Number: 92 01 37Y00 0 S J 2 0

Series: 92  
 Type: Extender  
 Insulator planform: 37Y  
 Polarisation: Standard  
 Gender: Socket/Female  
 Cable clamp: J (18-25mm)  
 Finish: Black (non-conductive)  
 Seal protection: Standard

